
This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISI											
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED						
1	15-0206	ADDED .76 X 45° CHAMFER, ADDED NOTE 2, CH'D PIN DIAMETER WAS 2X Ø2.667 IS Ø2.7432.	11/20/2015	RJC	JAG						
2	16-0047	REMOVED PINS AND DIM, ADDED ADDITIONAL VIEWS AND SQUARE END. CH'D SECTION LENGTH WAS 26 IS 25, CH'D MATERIAL WAS 1018/1020 IS 1018/1020 CR, CH'D FINISH WAS CAD PLATE YELLOW IS ZINC PLATE, CH'D NOTE 1 & 2, ADDED NOTE 3. ADDED ENGRAVE NOTE.	1/18/2016	SM	JAG						




ASSY QTY

ASSY QTY

UNIT

1 EXTERNAL SPLINE

B/O Part #




EXTERNAL SPLINE DATA INVOLUTE PROFILE SIDE FIT FILLET ROOT					
Pressure angle	30°				
MODULE	1.27				
NUMBER OF TEETH	12				
PITCH DIAMETER	15.240				
BASE DIAMETER	13.19823				
CIRCULAR SPACE THICKNESS (EFFECTIVE)	/				
CIRCULAR SPACE THICKNESS (ACTUAL)	1.880/1.900				
PINS DIAMETER	2.7432				
DIMENSION BETWEEN PINS	19.634/19.594				
MAJOR DIAMETER	16.500/16.400				
MINOR DIAMETER	12.590/12.460				
MAX T.I.F. DIAMETER	13.868				
MAX CUMULATIVE PITCH ERROR BETWEEN TWO TEETH	.036				
MAX PROFILE ERROR (TOTAL)	.008/013				
MAX PARALLEL (SM ERROR TOTAL)	.008				
mating spline	4G6320A11131				

Description

Material

1018/1020 CR

**B/O INFORMATION OR SPECIFICATIONS** 



- NOTE:
  1. ALL DIMENSIONS IN MILLIMETERS UNLESS SPECIFIED.
- 2. REF AGUSTA T/N: 3G6305G31351
- 3. PART OF KIT RBW6305G31231-3G

	3. 1 AKT OF KIT KB**0303C31231-3C								
	DART								
	SPLINED REACTION								
	DWG NO. RBW63050				G31351	2			
	MAT'L 1018/1020 CR HEAT TREAT				UNLESS OTHERWISE SPECIFIED  DIMENSIONS ARE IN INCHES  .XXX ± .005 FRACTIONS ± 1/8  .XX + .01 ANGLES ± .5°				
	FINISH ZINC F	FINISH ZINC PLATE			.XX ± .01	125/			
	SPEC ASTM B633 TYPE I SC 2			1. BREAK AL	$\vee$				
	DRAWN BY:	CLOUGH		.015 x 45° C	OR .015R NAL LIMITS APPLY				
	CHECKED:	DUERF	RFELDT		AFTER PLA	ATING			
	OPPS APPR: ANDERSON		3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009						
PG.	QA APPR:	LINDSAY		USED ON MODEL					
	APPROVED:	GILBERT		AW139					
1	SCALE	1:1	DATE	11/	17/2014	SHEET 1 OF	1		